



BP36V60ART2U EBM

The Extended Battery Module offers extended run-times during power outages.

The CyberPower BP36V60ART2U (36V) Extended Battery Module (EBM) with Fast Charge Technology provides extended battery run-time during power outages for select Smart App Online UPS models. Up to 10 EBMs can be added and fast charging times are maintained thanks to each EBM having a built in battery charger. The typical charging times of 5 hours for the OL1000RTXL2U and OL1500RTXL2U are maintained whether there are 1 or 10 EBMs installed.

Each EBM takes up 2U of rack space and can also be installed in a tower form factor to match the UPS. A DC plug-n-play power connector makes it easy to daisy-chain additional EBMs to a UPS system.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship.

Compatible Applications

- OL1000RTXL2U
- OL1500RTXL2U

Features

- 36V / 60A Output
- Fast Charge Technology
- Daisy-chain Power Connections
- Expandable Battery Modules
- Plug-n-Play DC Connectors
- 2U Rack/Tower Form Factor
- 3-Year Warranty

BP36V60ART2U EBM

The Extended Battery Module offers extended run-times during power outages.

GENERAL	
Voltage	36V
Amperage	60A
BATTERY	
Battery Type	Sealed Lead-Acid
Battery Size	12V/9AH
Hot-Swappable	Yes
Battery Quantity	6
User Replaceable	Yes
Typical Recharge Time	5 Hours
Built-in Charger	Yes
Expansion Ready (Daisy-Chain)	Yes
PHYSICAL	
Rack Size	2U
Mounting Hardware	Included
Enclosure Construction	Steel
Dimensions (WxHxD) (in.)	17 x 3.5 x 16.9
Dimensions (WxHxD) (mm.)	433 x 88 x 430
Weight (lbs.)	50.6
Weight (kg.)	22.9
Shipping Dimensions (WxHxD) (in.)	21.65 x 9.45 x 23.23
Shipping Dimensions (WxHxD) (mm.)	550 x 240 x 590
Shipping Weight (lbs.)	65.34
Shipping Weight (kg.)	29.6
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Relative Humidity	0% - 90% non-condensing
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5°F to 113°F / -15°C to 45°C
Storage Relative Humidity	0% - 95% non-condensing
Storage Elevation	0-50000 feet (0-15000 meters)
CERTIFICATIONS	
Safety	UL1778, CSA C22.2 NO.107.3-05, FCC DOC Class A
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited