CyberPower



CPS150BURC1 Mobile Power Inverter

Offering household power on the go.

The CPS150BURC1 mobile power inverter with 2.1A Quick Charge Technology converts 12v DC power to standard 120V AC power and provides fast USB charging for power hungry devices. Simply plug the inverter into a 12v DC outlet (cigarette lighter outlet) and you're ready to go.

It is equipped with one (1) NEMA 5-15R outlet and has a convenient 2.1A USB port for charging tablets, smart phones, MP3 players, and digital cameras.

It has Soft Start Technology that guards against power fluctuations from vehicle startup and shutdown. Its compact design and convenient 150-degree swivel head is designed to fit in all universal cigarette lighter receptacles and lets you power electronics on the road or even on a boat.

A Two-Year Warranty ensures that this product has passed our highest quality standards in design, assembly, material and workmanship.

Typical Applications

- Tablets
- Laptops
- Smartphones

Features

- 150W Power Inverter
- 150° Swivel Head
- (1) USB 2.1 Amp Charging Port
- (1) 120Vac Outlet
- Soft Start Technology
- 2-Year Warranty

CPS150BURC1 Mobile Power Inverter

Offering household power on the go.

GENERAL	
Product Type	Power Inverter
INPUT	
Voltage	10.5Vdc – 15.5Vdc
Current	15A max
Plug Type	12Vdc Auto Power Port
Plug Style	150° Swivel Head
OUTPUT	
Watts - Continuous	120
Watts - Peak	150
On Battery Voltage	120Vac
On Battery Frequency	60Hz
On Battery Waveform	Simulated Sine Wave
Outlets - Total	1
Outlet Type	NEMA 5-15R
USB Charge Port - Total	1
USB Charging Amperage	2.1A
PHYSICAL	
Color	Black/Gray
Form Factor	Direct Plug
Form Factor Enclosure Construction	Direct Plug ABS
Enclosure Construction	ABS
Enclosure Construction Dimensions (WxHxD) (in.)	ABS 3.6 x 5.4 x 1.4
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.)	ABS 3.6 x 5.4 x 1.4 0.29
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.)	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.) Shipping Weight (lbs.)	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.) Shipping Weight (lbs.) ENVIRONMENTAL	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2 0.47
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.) Shipping Weight (lbs.) ENVIRONMENTAL Operating Temperature	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2 0.47 32°F to 95°F / 0°C to 35°C
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.) Shipping Weight (lbs.) ENVIRONMENTAL Operating Temperature Operating Relative Humidity	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2 0.47 32°F to 95°F / 0°C to 35°C 0% - 95% non-condensing
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.) Shipping Weight (lbs.) ENVIRONMENTAL Operating Temperature Operating Relative Humidity Storage Temperature	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2 0.47 32°F to 95°F / 0°C to 35°C 0% - 95% non-condensing 5°F to 113°F / -15°C to 45°C
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.) Shipping Weight (lbs.) ENVIRONMENTAL Operating Temperature Operating Relative Humidity Storage Temperature Maximum Operating Elevation	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2 0.47 32°F to 95°F / 0°C to 35°C 0% - 95% non-condensing 5°F to 113°F / -15°C to 45°C 10,000 ft / 3,000 m
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.) Shipping Weight (lbs.) ENVIRONMENTAL Operating Temperature Operating Relative Humidity Storage Temperature Maximum Operating Elevation Maximum Storage Elevation	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2 0.47 32°F to 95°F / 0°C to 35°C 0% - 95% non-condensing 5°F to 113°F / -15°C to 45°C 10,000 ft / 3,000 m
Enclosure Construction Dimensions (WxHxD) (in.) Weight (lbs.) Shipping Dim. (WxHxD) (in.) Shipping Weight (lbs.) ENVIRONMENTAL Operating Temperature Operating Relative Humidity Storage Temperature Maximum Operating Elevation Maximum Storage Elevation CERTIFICATIONS	ABS 3.6 x 5.4 x 1.4 0.29 6.3 x 9.3 x 2 0.47 32°F to 95°F / 0°C to 35°C 0% - 95% non-condensing 5°F to 113°F / -15°C to 45°C 10,000 ft / 3,000 m 50,000 ft / 15,000 m