## **CyberPower**



### **CSP100TW Professional Surge Protector**

Offering home/office environments with computer and communication grade surge protection.

The CyberPower Professional Series CSP100TW Surge Protector is ideal for Home/Office protection with 900 joules, 1 outlet, and wall tap plug. The single outlet surge protector is perfect for environments were only a single device will require power protection. Its works great for protecting personal computers, wireless/VoIP routers, cable/ DSL modems, tablet chargers and other personal electronics.

The CSP100TW features one (1) outlet, a wall tap plug for direct plug in, MOV technology to guard the surge protector and connected electronics against line abnormalities and lightning surges, while EMI/RFI filters block unwanted line noise. Data line protection is provided via RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines.

A Limited Lifetime Warranty ensures that this surge protector has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$25,000 Connected Equipment Guarantee.

#### **Typical Applications**

- Desktop Computers
- Routers & Modems
- Personal Electronics

#### Features

- 1 Surge Protected Outlet
- 900 Joules of Surge Protection
- DSL / Phone / Fax Protection RJ11
- Compact Design
- Wall Tap Plug
- EMI/RFI Noise Filters
- Lifetime Warranty

# **CSP100TW Professional Surge Protector** Offering home/office environments with computer and communication grade surge protection.

GENERAL	
Product Type	Surge Protector
INPUT	
Voltage	125V
Plug Type	NEMA 5-15P
Plug Style	Wall Tap
OUTPUT	
Outlets - Total	1
Outlet Type	NEMA 5-15R
Outlets - Widely Spaced	1
SURGE PROTECTION & FILTERING	
Surge Suppression	900 Joules
Maximum Surge Current	45,000 Amps
Maximum Surge Current H-N	15,000 Amps
Maximum Surge Current H-G	15,000 Amps
Maximum Surge Current N-G	15,000 Amps
Clamping Voltage	800V (L-N, L-G, N-G)
Response Time	< 1 nanosecond
Phone Protection RJ11	1-In, 1-Out
EMI/RFI Filtration	150KHz to 100MHz
Attenuation	Up to 32dB
INDICATORS	
Indicators	Protected (Green)
CERTIFICATIONS	
Safety	UL1449 3rd Edition, cUL
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Limited Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$25,000