



PDU20B10R Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower 10-outlet rack mount basic power distribution unit (PDU20B10R) provides 120V 20A output. It distributes power to 10 NEMA 5-20R receptacles from a single NEMA 5-20P input, with unfiltered electrical pass-through.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 15-foot AC power cord. It can be mounted either horizontally or vertically, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

Typical Applications

- Servers
- Network Devices
- Telecom Equipment

Features

- Basic PDU
- Switch-Free Design
- Industrial-Grade Metal Housing
- Lifetime Warranty

PDU20B10R Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

GENERAL	
Type	Basic PDU
Phase	Single Phase
INPUT	
Voltage	120V
Current	20A max
Frequency	50Hz/60Hz
Plug Type	NEMA 5-20P
Plug Style	Straight
Cord Length	15'
OUTPUT	
Nominal Output Voltage	120V
Outlets - Total	10
Outlet Type	NEMA 5-20R
Outlets - Front	0
Outlets - Rear	10
Overload Protection	20A
PHYSICAL	
Rack Size	1U
Form Factors Supported	1U Rackmount, 0U Vertical Rackmount, Undercounter Installation Supported
Cord Retention Organizers	Yes
External Site Ground Pin	Yes
Adjustable Mounting Brackets	2 sets (L-short, L-long)
Dimensions (WxHxD) (in.)	17.5 x 1.75 x 1.5
Weight (lbs.)	4.5
ENVIRONMENTAL	
Operating Temperature	32°F to 95°F / 0°C to 35°C
Operating Relative Humidity	0% - 95% non-condensing
Storage Temperature	5°F to 113°F / -15°C to 45°C
Maximum Operating Elevation	10,000 ft / 3,000 m
Maximum Storage Elevation	50,000 ft / 15,000 m
CERTIFICATIONS	
Safety	UL1363 certified by ETL (USA), CSA C22.2 (Canada)
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Lifetime