

## Isobar 2-Outlet Surge Protector, Direct Plug-In, 1410 Joules, Diagnostic LEDs, Metal Housing

MODEL NUMBER: ISOBLOK2-0



Premium protection for A/V home theater components and computer peripherals against dangerous power surges, spikes and line noise. Recommended for home theaters and home offices.

### Description

Premium protection for your expensive computer and audio/visual equipment, the ISOBLOK2-0 Isobar® 2-Outlet Surge Protector features a surge protection rating of 1410 joules to defend your sensitive electronics against even the strongest surges and spikes.

The ISOBLOK2-0 features two NEMA 5-15R outlets, perfect for your flat-panel HDTV and Blu-ray™ player or a pair of computer peripherals, such as a printer and a router. This unit's unique protection system prevents disruptive line noise from causing A/V distortion, computer lock-ups, data errors and similar problems. Large toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors remove EMI/RFI interference and prevent system crashes, reboots and performance problems.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the ISOBLOK2-0 protects all three, covering two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

Diagnostic LEDs show power, protection and line fault status at a glance. The ISOBLOK2-0 plugs directly into any standard NEMA 5-15R outlet. Optional mounting hardware is included for permanent attachment to the outlet cover, which will prevent the ISOBLOK2-0 from coming loose accidentally.

### Features

#### 1410-Joule Surge Protection for Your Home Theater Electronics and Computer Peripherals

- Protects your components against surges and spikes
- Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- 2 NEMA 5-15R surge-protected outlets

#### Premium Safety Features

- Diagnostic LEDs confirm power, protection and ground status at a glance
- Conforms to current UL 1449 3rd Edition safety standards
- Auto shutoff cuts power to outlets when the protection circuit is compromised

#### Fits Effortlessly Into Your Setup

- Plugs directly into standard NEMA 5-15R outlet with no power cord
- Optional hardware included for permanent mounting to outlet cover
- Metal housing designed for long life

### Highlights

- 2 NEMA 5-15R surge-protected outlets
- 1410-joule surge protection rating
- Durable metal housing mounts out of sight behind furniture
- LEDs indicate power, protection and line fault status
- Plugs directly into outlet with no power cord

### Package Includes

- ISOBLOK2-0 Isobar 2-Outlet Surge Protector, Metal Housing
- Mounting hardware
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

**Backed by Ultimate Lifetime Insurance**

- \$10,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

## Specifications

| OVERVIEW                            |                                                                              |
|-------------------------------------|------------------------------------------------------------------------------|
| UPC Code                            | 037332010155                                                                 |
| INPUT                               |                                                                              |
| Nominal Input Voltage(s) Supported  | 120V AC                                                                      |
| Recommended Electrical Service      | 120V (110-125V)                                                              |
| Input Cord Length Details           | Direct Plug-In                                                               |
| Voltage Compatibility (VAC)         | 120                                                                          |
| Input Plug Type                     | NEMA 5-15P                                                                   |
| Input Cord Length (ft.)             | 0                                                                            |
| Right-Angle Plug                    | No                                                                           |
| Input Cord Length (m)               | 0.00                                                                         |
| Integrated Cord Clip                | No                                                                           |
| OUTPUT                              |                                                                              |
| Frequency Compatibility             | 50 / 60 Hz                                                                   |
| Output (Watts)                      | 1800                                                                         |
| Output Receptacles                  | (2) 5-15R                                                                    |
| Circuit Breaker (amps)              | 15                                                                           |
| Right-Angle Outlets                 | No                                                                           |
| USER INTERFACE, ALERTS & CONTROLS   |                                                                              |
| Diagnostic LED(s)                   | Yes                                                                          |
| Diagnostic LED Details              | PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)             |
| SURGE / NOISE SUPPRESSION           |                                                                              |
| AC Suppression Joule Rating         | 1410                                                                         |
| AC Suppression Response Time        | NM = 0 ns. CM = <1 ns                                                        |
| Protection Modes                    | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| AC Suppression Surge Current Rating | 48,000 amps                                                                  |
| AC Suppression Components Used      | Metal oxide varistors, toroidal balanced chokes and VHF capacitors           |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                                                                                           |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Safe Thermal Fusing                  | Prevents unsafe conditions during extreme extended overvoltages and catastrophic occurrences              |
| UL1449 Let Through Rating            | 330V                                                                                                      |
| EMI / RFI Filtering                  | 40-80 dB                                                                                                  |
| Isolated Filter Banks                | y                                                                                                         |
| Immunity                             | Conforms to IEE 587 / ANSI C62.41                                                                         |
| Automatic Shut-Off                   | No                                                                                                        |
| <b>DATALINE SURGE SUPPRESSION</b>    |                                                                                                           |
| Cable (Coax) Protection              | No                                                                                                        |
| Network (Ethernet) Protection        | No                                                                                                        |
| Telephone/DSL Protection             | No                                                                                                        |
| <b>PHYSICAL</b>                      |                                                                                                           |
| Material of Construction             | Metal                                                                                                     |
| Form Factors Supported               | Direct plug-in format with retaining bracket supports wall mounting directly to a standard AC wall socket |
| Housing Color                        | Gray                                                                                                      |
| Mounting Holes or Slots              | No                                                                                                        |
| Receptacle Color                     | Black                                                                                                     |
| Shipping Dimensions (hwd / in.)      | 2.50 x 6.00 x 3.90                                                                                        |
| Shipping Dimensions (hwd / cm)       | 6.35 x 15.24 x 9.91                                                                                       |
| Shipping Weight (lbs.)               | 0.80                                                                                                      |
| Shipping Weight (kg)                 | 0.36                                                                                                      |
| Unit Dimensions (hwd / in.)          | 4.000 x 2.500 x 2.500                                                                                     |
| Unit Dimensions (hwd / cm)           | 10.2 x 6.4 x 6.4                                                                                          |
| Unit Weight (lbs.)                   | 0.8                                                                                                       |
| Unit Weight (kg)                     | 0.36                                                                                                      |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                                                                                           |
| Rotatable Outlets                    | No                                                                                                        |
| Antimicrobial                        | No                                                                                                        |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                                                                                           |
| Product Certifications               | NOM (Mexico); UL 1449; UL 1363                                                                            |
| Product Compliance                   | RoHS                                                                                                      |
| <b>WARRANTY &amp; SUPPORT</b>        |                                                                                                           |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty                                                                                 |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                               |                                                                                                                         |
|---------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$10,000 <a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |
|---------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.