

## 3.7kW Single-Phase Local Metered PDU, 208/230V Outlets (8 C13, 2 C19) IEC-309 16A Blue, 8 ft. (2.43 m) Cord, 1U Rack-Mount, TAA

MODEL NUMBER: PDUMH16HV



### Highlights

- Local metered single phase 16A 208/230V PDU
- 1U horizontal rackmount; digital current meter
- C20 input with IEC-309 Blue 16A input; 2.5m line cord
- 10 total outlets (8 C13, 2 C19); 6.5 in. / 16.5 cm depth
- TAA Compliant

### Package Includes

- Rackmount PDU
- Rack mounting brackets
- Plug lock inserts
- IEC-309 Blue 16A input cord

### Features

- 3.7kW 16A single phase 208/230V Local Metered Power Distribution Unit / rack PDU (rPDU)
- Built-in 2 digit visual meter continuously reports PDU load level in amps
- C20 inlet with IEC-309 Blue 16A input; 2.5m line cord
- 1U horizontal rackmount format installs in one rack space
- 10 total outlets (8 C13 / 2 C19)
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Front panel grounding lug
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

| OVERVIEW                       |                                      |
|--------------------------------|--------------------------------------|
| UPC Code                       | 037332182791                         |
| PDU Type                       | Local Metered                        |
| INPUT                          |                                      |
| Input Phase                    | Single-Phase                         |
| PDU Input Voltage              | 208; 230                             |
| Recommended Electrical Service | Single-phase 16/20A 230/208V service |
| Maximum Input Amps             | 16                                   |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                                                                                                          |
|----------------------------------------------|----------------------------------------------------------------------------------------------------------|
| PDU Plug Type                                | IEC-60309 16A BLUE (2P+E)                                                                                |
| Input Cord Length (ft.)                      | 8.2                                                                                                      |
| Input Cord Length (m)                        | 2.50                                                                                                     |
| <b>OUTPUT</b>                                |                                                                                                          |
| Output Capacity Details                      | 3.7kW (230V), 3.3kW (208V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet |
| Frequency Compatibility                      | 50 / 60 Hz                                                                                               |
| Output Receptacles                           | (8) C13; (2) C19                                                                                         |
| Output Nominal Voltage                       | 208/230V                                                                                                 |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                                                                          |
| Front Panel LCD Display                      | Digital display reports total PDU output current in amps                                                 |
| <b>SURGE / NOISE SUPPRESSION</b>             |                                                                                                          |
| Automatic Shut-Off                           | No                                                                                                       |
| <b>PHYSICAL</b>                              |                                                                                                          |
| Material of Construction                     | Metal                                                                                                    |
| Rack Height                                  | 1U                                                                                                       |
| Form Factors Supported                       | 1U rackmount. Includes mounting accessories for 2-4 post racks                                           |
| Minimum Required Rack Depth (cm)             | 25.40                                                                                                    |
| Minimum Required Rack Depth (inches)         | 10                                                                                                       |
| PDU Form Factor                              | Horizontal (1U)                                                                                          |
| Shipping Dimensions (hwd / in.)              | 3.03 x 20.47 x 10.94                                                                                     |
| Shipping Dimensions (hwd / cm)               | 7.70 x 51.99 x 27.79                                                                                     |
| Shipping Weight (lbs.)                       | 6.50                                                                                                     |
| Shipping Weight (kg)                         | 2.95                                                                                                     |
| Unit Dimensions (hwd / in.)                  | 1.750 x 17.500 x 6.500                                                                                   |
| Unit Dimensions (hwd / cm)                   | 2.87 x 44.4 x 16.5                                                                                       |
| Unit Weight (lbs.)                           | 6.8                                                                                                      |
| Unit Weight (kg)                             | 3.08                                                                                                     |
| <b>ENVIRONMENTAL</b>                         |                                                                                                          |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)                                                                                |
| Storage Temperature Range                    | -22° to 122°F (-30° to 50°C)                                                                             |
| Relative Humidity                            | 5% to 95% non-condensing                                                                                 |
| Operating Elevation                          | 0-10000 ft. (0-3000 m)                                                                                   |



Powering Business Worldwide

TRIPP LITE  
SERIES

| FEATURES & SPECIFICATIONS           |                                                                                                             |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Grounding                           | Front panel grounding lug                                                                                   |
| STANDARDS & COMPLIANCE              |                                                                                                             |
| Product Certifications              | IEC 62368-1; RETIE (Colombia); GOST (Russia); NOM (Mexico)                                                  |
| Product Compliance                  | RoHS; CE (Europe); EAC (Belarus, Kazakhstan, Russia); FCC Part 15 Class A (USA); Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT                  |                                                                                                             |
| Product Warranty Period (Worldwide) | 2-year limited warranty                                                                                     |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.