

## 2.4kW Single-Phase Local Metered PDU, 120V (12 5-15/20R), L5-20P / 5-20P, 120V Input, 15 ft. (4.57 m) Cord, 1U Rack-Mount

MODEL NUMBER: PDUMH20



### Highlights

- Local metered single phase 20A 120V PDU
- 1U horizontal rackmount; digital current meter
- NEMA 5-20P / L5-20P input; 15-ft. (4.57 m) line cord
- 12 NEMA 5-15/20R outlets
- Reversible housing; 4.5 in. / 11.4cm depth

### Package Includes

- PDUMH20 Local Metered rackmount PDU
- L5-20R to 5-20P plug adapter
- Owner's manual with warranty information

### Features

- 20A single phase 120V Local Metered Power Distribution Unit / rack PDU (rPDU)
- Built-in 2 digit visual meter continuously reports PDU load level in amps
- Attached NEMA L5-20P 20A 120V input plug with 15-ft. (4.57 m) line cord
- Includes 5-20P 20A 120V plug adapter
- 1U horizontal rackmount format installs in one rack space
- 12 NEMA 5-15/20R outlets
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Optional PDUSIDEBRKT enables 0U vertical rackmount in compatible racks
- Back panel grounding lug

## Specifications

| OVERVIEW                       |                               |
|--------------------------------|-------------------------------|
| UPC Code                       | 037332142504                  |
| PDU Type                       | Local Metered                 |
| INPUT                          |                               |
| Input Phase                    | Single-Phase                  |
| PDU Input Voltage              | 120                           |
| Recommended Electrical Service | Single-phase 20A 120V service |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                                                                                 |
|----------------------------------------------|---------------------------------------------------------------------------------|
| Maximum Input Amps                           | 20                                                                              |
| PDU Plug Type                                | NEMA 5-20P; NEMA L5-20P                                                         |
| Input Cord Length (ft.)                      | 15                                                                              |
| Input Cord Length (m)                        | 4.57                                                                            |
| <b>OUTPUT</b>                                |                                                                                 |
| Output Capacity Details                      | 2.4kW (120V) / 20A total capacity; 16A max per outlet                           |
| Frequency Compatibility                      | 50 / 60 Hz                                                                      |
| Output Receptacles                           | (12) 5-15/20R                                                                   |
| Output Nominal Voltage                       | 120V                                                                            |
| Overload Protection                          | 20A circuit breaker                                                             |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                                                 |
| Front Panel LCD Display                      | Digital display reports total PDU output current in amps                        |
| <b>SURGE / NOISE SUPPRESSION</b>             |                                                                                 |
| Automatic Shut-Off                           | No                                                                              |
| <b>PHYSICAL</b>                              |                                                                                 |
| Material of Construction                     | Metal                                                                           |
| Rack Height                                  | 1U                                                                              |
| Form Factors Supported                       | 1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation |
| Minimum Required Rack Depth (cm)             | 24.13                                                                           |
| Minimum Required Rack Depth (inches)         | 9.5                                                                             |
| Outlets Measurement (Center to Center)       | 30.20mm                                                                         |
| PDU Form Factor                              | Horizontal (1U)                                                                 |
| Shipping Dimensions (hwd / in.)              | 9.20 x 2.25 x 20.40                                                             |
| Shipping Dimensions (hwd / cm)               | 23.37 x 5.72 x 51.82                                                            |
| Shipping Weight (lbs.)                       | 6.40                                                                            |
| Shipping Weight (kg)                         | 2.90                                                                            |
| Unit Dimensions (hwd / in.)                  | 2.000 x 20.000 x 4.500                                                          |
| Unit Dimensions (hwd / cm)                   | 4.45 x 44.5 x 11.4                                                              |
| Unit Weight (lbs.)                           | 3                                                                               |
| Unit Weight (kg)                             | 1.36                                                                            |
| <b>ENVIRONMENTAL</b>                         |                                                                                 |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)                                                       |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                            |
|--------------------------------------|--------------------------------------------|
| Storage Temperature Range            | -22° to 122°F (-30° to 50°C)               |
| Relative Humidity                    | 5% to 95% non-condensing                   |
| Operating Elevation                  | 0-10000 ft. (0-3000 m)                     |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                            |
| Grounding                            | Back panel grounding lug                   |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                            |
| Product Certifications               | RETIE (Colombia); NOM (Mexico); UL 60950-1 |
| Product Compliance                   | RoHS                                       |
| <b>WARRANTY &amp; SUPPORT</b>        |                                            |
| Product Warranty Period (Worldwide)  | 2-year limited warranty                    |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.