


## 375W PowerVerter Ultra-Compact Car Inverter with 2 Outlets

MODEL NUMBER: **PV375**



### Highlights

- 12V DC input; 120V AC output; 2 outlets
- 375 watts continuous output
- 600 watts peak output (instantaneous)
- Convenient cigarette lighter plug

### Package Includes

- PV375 Inverter
- Warranty information
- Instruction manual

### Description

Utilize your vehicle's battery to efficiently power office equipment on the road. Continuously supplies up to 375 watts of 120V AC power to 2 AC outlets from any 12V battery or automotive DC source. Convenient cigarette lighter DC input jack with 3-ft. (0.91 m) cable provides 1-step installation. Portable and compact, the inverter's design is among the most rugged available thanks to its lightweight metal casing.

### Features

- Allows users to run AC devices from any 12V cigarette lighter socket
- Converts 12V DC battery power to 120V AC power
- 375 watts continuous output power; 600 watts peak output power (instantaneous)
- 2 outlets
- 3-ft. (0.91 m) cord with cigarette lighter plug
- Ultra compact, lightweight design with all-metal housing
- Low battery alarm with auto-shutoff preserves vehicle battery
- Overload alarm with auto-shutoff prevents wattage overload
- Replaceable 40amp fuse protects inverter from overload
- Lighted power switch

## Specifications

| OVERVIEW                   |                                                                 |
|----------------------------|-----------------------------------------------------------------|
| UPC Code                   | 037332119841                                                    |
| INPUT                      |                                                                 |
| Maximum Input Amps / Watts | Full continuous load - 40A at 12V DC, No load - 0.65A at 12V DC |
| Input Connection Type      | 12V DC cigarette lighter input plug connection                  |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                                                                                             |
|----------------------------------------------|---------------------------------------------------------------------------------------------|
| Input Cord Length Details                    | 3 ft. hardwire input cable, 16 gauge, 2 wire                                                |
| Voltage Compatibility (VDC)                  | 12                                                                                          |
| <b>OUTPUT</b>                                |                                                                                             |
| Frequency Compatibility                      | 60 Hz                                                                                       |
| Pure Sine Wave Output                        | No                                                                                          |
| Output (Watts)                               | 375                                                                                         |
| Nominal Output Voltage(s) Supported          | 120V                                                                                        |
| Output Receptacles                           | (2) 5-15R                                                                                   |
| Continuous Output Capacity (Watts)           | 375                                                                                         |
| Peak Output Capacity (Watts)                 | 600                                                                                         |
| Output Voltage Regulation                    | Maintains PWM sine wave output voltage of 115 V AC (+/- 8 VAC)                              |
| Output Frequency Regulation                  | 60 Hz (+/- 3 Hz)                                                                            |
| Overload Protection                          | 40A automotive input fuse                                                                   |
| <b>BATTERY</b>                               |                                                                                             |
| DC System Voltage (VDC)                      | 12                                                                                          |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                                                             |
| Switches                                     | Lighted on/off power switch                                                                 |
| Audible Alarm                                | Dual function alarm indicates overload conditions or low DC input voltage of 10.5V or less. |
| <b>PHYSICAL</b>                              |                                                                                             |
| Material of Construction                     | Aluminum, Steel                                                                             |
| Cooling Method                               | Fan                                                                                         |
| Shipping Dimensions (hwd / in.)              | 2.50 x 5.80 x 7.70                                                                          |
| Shipping Dimensions (hwd / cm)               | 6.35 x 14.73 x 19.56                                                                        |
| Shipping Weight (lbs.)                       | 2.18                                                                                        |
| Shipping Weight (kg)                         | 0.99                                                                                        |
| Unit Dimensions (hwd / in.)                  | 2.000 x 4.250 x 7.000                                                                       |
| Unit Dimensions (hwd / cm)                   | 5.08 x 10.8 x 17.78                                                                         |
| Unit Weight (lbs.)                           | 2.3                                                                                         |
| Unit Weight (kg)                             | 1.04                                                                                        |
| <b>ENVIRONMENTAL</b>                         |                                                                                             |
| Relative Humidity                            | 0-95% non-condensing                                                                        |
| <b>STANDARDS &amp; COMPLIANCE</b>            |                                                                                             |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |                         |
|-------------------------------------|-------------------------|
| Product Compliance                  | RoHS                    |
| <b>WARRANTY &amp; SUPPORT</b>       |                         |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.