

## SmartPro 1500VA 1500W 208V Line-Interactive Sine Wave UPS - 8 Outlets, Extended Run, Network Card Included, LCD, USB, DB9, 2U Rack/Tower

MODEL NUMBER: **SMX1500XLRT2UN**



Provides complete battery backup and pure sine wave power output for servers, switches and other high-end distributed IT equipment.

### Features

#### 1.5kVA/1.5kW/208V Battery Backup for Distributed IT, Telecom or Enterprise Deployments

This rack-mount line-interactive UPS system provides reliable battery backup and AC power protection against blackouts, brownouts, surges and line noise that can damage your valuable IT equipment or destroy data. The SMX1500XLRT2UN is ideal power management for high-end in-rack networking equipment, including servers, VoIP phones, data storage and PoE switches. Unity power factor ensures the most watts possible at each power rating, so you can connect more equipment.

#### Reliable, Expandable Battery Backup Keeps You Operational Through Power Outages

The field-replaceable, hot-swappable VRLA internal battery modules allow you to work through short power failures and give you enough time to safely save files and shut down your system in case of a prolonged blackout. Switchover from line to battery power happens within milliseconds to maintain continuous operation of connected equipment without interruption or rebooting. Extra runtime is available by connecting up to four optional extended battery modules (BP48VRM2U, sold separately).

#### Pre-Installed LX Platform Network Management Card Allows Remote Access 24/7

The WEBCARDLXE network interface enables full remote configuration and management, including load shedding, reboots of connected equipment and safe shutdowns. The IP-based Auto Probe feature ensures continuous network uptime by communicating with other network devices, detecting lost connectivity and automatically rebooting IT equipment. Optional EnviroSense2 modules (E2MT, E2MTDO and E2MTHDI, all sold separately) provide a variety of environmental monitoring and control options.

#### C13 Outlets Protect Your Connected Components

Eight C13 outlets provide connected equipment with pure sine wave AC output and allow you to monitor power consumption down to the outlet group level. Power provided by these outlets is filtered to protect connected equipment against damaging surges and line noise. Four outlets are grouped into two programmable load banks that let you shed non-critical loads to extend runtime for critical loads. Front and rear cooling fans help protect equipment from overheating.

#### Automatic Voltage Regulation (AVR) Corrects Low- and High-Voltage Conditions

AVR protects your equipment from incremental hardware damage, data loss and performance problems caused by brownouts. The SMX1500XLRT2UN maintains regulated 208V nominal output during

### Highlights

- Protects equipment against blackouts, brownouts, transient surges and line noise
- Keeps equipment running during outages to allow time for file saves and safe shutdown
- Unity power factor ensures maximum power possible at each power rating
- Included WEBCARDLXE network interface allows 24/7 remote access and control
- 2-line front-panel LCD with 10 selectable screens reports detailed UPS and site power info

### Package Includes

- 1500VA 1500W 208V Line-Interactive UPS
- WEBCARDLXE network management card
- USB cable
- DB9 cable
- Rack-mounting hardware
- Tower support stands
- Safety instructions
- Advanced User Guide



Powering Business Worldwide

TRIPP LITE  
SERIES

brownouts and overvoltages from 160V to 294V while keeping the battery fully charged and ready to take over in case of power failure.

#### Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

This UPS system filters out disruptive electromagnetic and radio frequency interference that can inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

#### ENERGY STAR-Certified to Help You Save Money and Protect the Environment

By meeting strict U.S. Department of Energy and U.S. Environmental Protection Agency requirements, this ENERGY STAR 2.0 UPS system provides high operational efficiency to signal a reduction in BTU emissions, save on utility and cooling costs and help protect the environment.

#### Intuitive Front-Panel Interface for Convenient UPS Operation and Monitoring

The two-line front-panel LCD monitoring screen features 10 selectable screens that allow quick access to a wide range of detailed UPS and site power information. LEDs show UPS status: a green light means utility power is on, an orange light means the UPS is in battery mode and a red light indicates an active alarm or fault. The control panel rotates to accommodate both rack-mount and tower configurations.

#### Advanced Communications Ports Allow for Automatic Saves and Shutdowns

RS-232 and USB ports connect to a device for a variety of communication options (cables are included). A dry-contact relay port can be programmed through the LCD to provide reliable communications to automation and industrial components. The RPO/ROO port permits emergency shutdown or remote restart of all connected equipment.

#### Versatile Installation Options

You can mount the SMX1500XLRT2UN in just 2U of space in an EIA-standard 19-inch rack using the included hardware. You can also adapt it for tower installation using the included support stands. The C14 input accepts a variety of detachable cordsets to match country- or site-specific wall outlets.

## Specifications

| OVERVIEW                           |                                                                                                                         |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| UPC Code                           | 037332256423                                                                                                            |
| UPS Type                           | Line-Interactive                                                                                                        |
| INPUT                              |                                                                                                                         |
| Input Phase                        | Single-Phase                                                                                                            |
| Rated input current (Maximum Load) | 10A                                                                                                                     |
| Nominal Input Voltage(s) Supported | 208V AC                                                                                                                 |
| UPS Input Connection Type          | C14 inlet                                                                                                               |
| UPS Input Connection Description   | IEC320-C14 input connection accepts a variety of detachable cordsets to match country or site-specific wall receptacles |
| Maximum Input Amps                 | 10                                                                                                                      |
| OUTPUT                             |                                                                                                                         |
| Output Capacity (VA)               | 1500                                                                                                                    |
| Output Capacity (kVA)              | 1.5                                                                                                                     |
| Output Capacity (Watts)            | 1500                                                                                                                    |



|                                            |                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Output Capacity (kW)                       | 1.5                                                                                                                                                                                                                                                                                                                                                               |
| Power Factor                               | 1.0                                                                                                                                                                                                                                                                                                                                                               |
| Nominal Voltage Details                    | 208V nominal output in battery mode                                                                                                                                                                                                                                                                                                                               |
| Frequency Compatibility                    | 50 / 60 Hz                                                                                                                                                                                                                                                                                                                                                        |
| Frequency Compatibility Details            | Automatic frequency selection                                                                                                                                                                                                                                                                                                                                     |
| Output Voltage Regulation (Line Mode)      | 208V (-13%, +15%)                                                                                                                                                                                                                                                                                                                                                 |
| Output Voltage Regulation (Battery Mode)   | -10%, +6%                                                                                                                                                                                                                                                                                                                                                         |
| Included Output Power Cables               | Set of 2 C13 to C14 power cables included                                                                                                                                                                                                                                                                                                                         |
| Load Management Receptacles                | Two switchable two-outlet C13 load banks                                                                                                                                                                                                                                                                                                                          |
| Hot-Swap PDU options                       | PDUBHV10 (2U / 8 C13 outlets)                                                                                                                                                                                                                                                                                                                                     |
| Output AC Waveform (AC Mode)               | Sine wave                                                                                                                                                                                                                                                                                                                                                         |
| Output AC Waveform (Battery Mode)          | Pure Sine wave                                                                                                                                                                                                                                                                                                                                                    |
| Nominal Output Voltage(s) Supported        | 200V; 208V; 220V; 230V; 240V                                                                                                                                                                                                                                                                                                                                      |
| Output Receptacles                         | (8) C13                                                                                                                                                                                                                                                                                                                                                           |
| Individually Controllable Load Banks       | Yes                                                                                                                                                                                                                                                                                                                                                               |
| BATTERY                                    |                                                                                                                                                                                                                                                                                                                                                                   |
| Battery Type                               | Valve Regulated Lead Acid (VRLA)                                                                                                                                                                                                                                                                                                                                  |
| Runtime Full Load (min.)                   | 5 min. (1500W)                                                                                                                                                                                                                                                                                                                                                    |
| Runtime Half Load (min.)                   | 14 min. (750W)                                                                                                                                                                                                                                                                                                                                                    |
| Expandable Runtime                         | Yes                                                                                                                                                                                                                                                                                                                                                               |
| Expandable Battery Runtime                 | Extended runtime supported via optional external battery packs                                                                                                                                                                                                                                                                                                    |
| External Battery Pack Compatibility        | &nbsp;   <a class="productLink" href="//tripplite.eaton.com/eaton-tripp-lite-series-48v-battery-for-smartpro-ups-systems-2u~BP48VRM2U">BP48VRM2U</a>&nbsp;   (limit 4)                                                                                                                                                                                            |
| DC System Voltage (VDC)                    | 48                                                                                                                                                                                                                                                                                                                                                                |
| Battery Recharge Rate (Included Batteries) | Less than 4.5 hours from 10% to 90% (typical, full load discharge)                                                                                                                                                                                                                                                                                                |
| Battery Access                             | Front panel battery access door                                                                                                                                                                                                                                                                                                                                   |
| Internal UPS Replacement Battery Cartridge | Pre-December 2023: &nbsp;   <a class="productLink" href="//tripplite.eaton.com/2U-UPS-Replacement-36VDC-Battery-Cartridge-1-set-3-select-Tripp-Lite-SmartPro-UPS~RBC93-2U">RBC93-2U</a>&nbsp;   Post-January 2024: &nbsp;   <a class="productLink" href="//tripplite.eaton.com/Eaton-Internal-Replacement-Battery-1500VA-5PXG2-UPS~744-A4801">744-A4801</a>&nbsp; |
| Battery Replacement Description            | Hot-swappable, user replaceable batteries                                                                                                                                                                                                                                                                                                                         |
| VOLTAGE REGULATION                         |                                                                                                                                                                                                                                                                                                                                                                   |
| Voltage Regulation Description             | Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 150 to 294V                                                                                                                                                                                                                                                      |
| Overvoltage Correction                     | Reduces incoming voltage between 265-294V (Normal Mode / Extended Mode) by 13%                                                                                                                                                                                                                                                                                    |
| Undervoltage Correction                    | Increases incoming voltage between 162-184V (Normal Mode) or 151-184V (Extended Mode) by 15%                                                                                                                                                                                                                                                                      |



| USER INTERFACE, ALERTS & CONTROLS                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Front Panel LCD Display                                         | Front panel LCD information and configuration screen offers detailed UPS and site power status and operating data, plus configuration of voltage, operating mode, alarm function and a variety of additional options (see manual for detailed LCD configuration and monitoring options)                                                                                                                                                                                     |
| Switches                                                        | 5 pushbutton switches control OFF / ON power status, ENTER, UP, and DOWN selection and ESC control functions. LX Platform Interface: Recessed reset switch for interface reboot and factory reset                                                                                                                                                                                                                                                                           |
| Alarm Cancel Operation                                          | Press the ESC (Escape) button on the front panel display to silence the alarm. Check the alarm condition and perform the applicable action to resolve the condition. If the alarm status changes, the alarm beeps again, overriding the previous alarm silencing                                                                                                                                                                                                            |
| Audible Alarm                                                   | Audible alarm indicates UPS startup, power-failure, low-battery, overload, UPS fault and remote shutdown conditions                                                                                                                                                                                                                                                                                                                                                         |
| LED Indicators                                                  | UPS: 3 status-indicating LEDs (normal, battery mode, alarm/fault); LED colors (green = ON, orange = On battery, flashing orange = below warning level, red = alarm/fault). LX Platform Interface Status: Network Link/Activity (Green): Flashes for network activity. Network Speed (Yellow): 10 Mbps (Flashing), 100 Mbps (On steady). Normal Operation (Solid Green); Software Update (Alternating Green/Orange ~1/sec); Factory Reset (Alternating Green/Orange ~2/sec). |
| SURGE / NOISE SUPPRESSION                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| EMI / RFI AC Noise Suppression                                  | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| AC Suppression Joule Rating                                     | 175                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| AC Suppression Response Time                                    | Instantaneous                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| PHYSICAL                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Primary Form Factor                                             | Rackmount; Tower                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Rack Height                                                     | 2U                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Cooling Method                                                  | Fan                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Installation Form Factors Supported with Included Accessories   | 4 post 19 inch rackmount; Tower                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Installation Form Factors Supported with Optional Accessories   | 2 post rackmount (&nbsp;<a class="productLink" href="//tripplite.eaton.com/2-post-rack-mount-kit~103007018-5591">103007018-5591</a>&nbsp;); 2 post rackmount (&nbsp;<a class="productLink" href="//tripplite.eaton.com/2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM">2POSTRMKITWM</a>&nbsp;);                                                                                                                                        |
| Minimum Required Rack Depth (cm)                                | 53.34                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Minimum Required Rack Depth (inches)                            | 21                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Minimum Required Rack Depth with External Battery Pack (cm)     | 53                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Minimum Required Rack Depth with External Battery Pack (in.)    | 21                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Minimum Required Rack Depth without External Battery Pack (cm)  | 53                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Minimum Required Rack Depth without External Battery Pack (in.) | 21                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Optional Mounting Accessory Notes                               | Optional &nbsp;<a class="productLink" href="//tripplite.eaton.com/4-Post-1U-Universal-Adjustable-Rack-Mount-Shelf-Kit-for-Wall-Mount-Racks~4POSTRAILKITWM">4POSTRAILKITWM</a>&nbsp; enables installation in 4-post short-depth racks from 14.5 to 23.5 inches (368 to 597mm)                                                                                                                                                                                                |
| Primary UPS Depth (mm)                                          | 447                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Primary UPS Height (mm)                                         | 86                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                    |                                                                                                                                                                                                                                       |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Primary UPS Width (mm)                             | 437                                                                                                                                                                                                                                   |
| Shipping Dimensions (hwd / in.)                    | 9.40 x 19.60 x 23.00                                                                                                                                                                                                                  |
| Shipping Weight (kg)                               | 27.90                                                                                                                                                                                                                                 |
| UPS Housing Material                               | Steel                                                                                                                                                                                                                                 |
| UPS Power Module Dimensions (hwd, in.)             | 3.4 x 17.2 x 17.6                                                                                                                                                                                                                     |
| UPS Power Module Weight (kg)                       | 20.18                                                                                                                                                                                                                                 |
| UPS Power Module Weight (lbs.)                     | 44.5                                                                                                                                                                                                                                  |
| Unit Dimensions (hwd / in.)                        | 3.400 x 17.200 x 17.600                                                                                                                                                                                                               |
| Unit Weight (lbs.)                                 | 49.4                                                                                                                                                                                                                                  |
| Unit Weight (kg)                                   | 22.41                                                                                                                                                                                                                                 |
| Mounting Details                                   | Included mounting bracket enables installation in 4 post racks. Two ABS mounting stands enables the UPS to be configured in an upright tower orientation.                                                                             |
| <b>ENVIRONMENTAL</b>                               |                                                                                                                                                                                                                                       |
| Operating Temperature Range                        | 32° to 104°F (0° to 40°C)                                                                                                                                                                                                             |
| Storage Temperature Range                          | 5° to 122°F (-15° to 50°C)                                                                                                                                                                                                            |
| Relative Humidity                                  | 20 to 95%, non-condensing                                                                                                                                                                                                             |
| AC Mode BTU / Hr. (Full Load)                      | 106                                                                                                                                                                                                                                   |
| AC Mode Efficiency Rating (100% Load)              | 98%                                                                                                                                                                                                                                   |
| Battery Mode Heat Dissipation (BTU/Hr) @ Full Load | 699                                                                                                                                                                                                                                   |
| Operating Elevation                                | 0-10000 ft. (0-3000 m)                                                                                                                                                                                                                |
| Storage Elevation (ft.)                            | 0-32,808                                                                                                                                                                                                                              |
| Audible Noise                                      | 45 dBA maximum, front side 1m                                                                                                                                                                                                         |
| Storage Elevation (m)                              | 0-10,000                                                                                                                                                                                                                              |
| <b>COMMUNICATIONS</b>                              |                                                                                                                                                                                                                                       |
| Network Management Cards                           | &nbsp;<a class="productLink" href="//tripplite.eaton.com/Network-Card-Eaton-Tripp-Lite-Series-UPS-Systems~WEBCARDLXE">WEBCARDLXE</a>&nbsp;                                                                                            |
| Network Monitoring Port Description                | Pre-installed WEBCARDLXE supports detailed monitoring and management of UPS and site power conditions. Not compatible with WEBCARDLX.                                                                                                 |
| PowerAlert Software                                | For local monitoring via the UPS's built-in communication ports, download PowerAlert Office software at <a href="https://tripplite.eaton.com/poweralert">https://tripplite.eaton.com/poweralert</a>                                   |
| Communications Cable                               | Micro-USB, USB and DB9 cabling included                                                                                                                                                                                               |
| Network Monitoring Port                            | RJ45 Network port, Micro-USB Configuration/Console port, USB A port supports a variety of Envirosense2 environmental and control modules. See Accessories>Management Hardware section for more information about these modules.       |
| SNMP Compatibility                                 | SNMP V1, V2c, V3                                                                                                                                                                                                                      |
| Network UPS Tools (NUT) Compatibility              | NUT compatible. See a full list of NUT compatible Tripp Lite UPS systems at <a href="https://networkupstools.org/stable-hcl.html?manufacturer=Tripp%20Lite">https://networkupstools.org/stable-hcl.html?manufacturer=Tripp%20Lite</a> |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                             |                                                                                                                                                                                                          |
|-------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network Compatibility                                       | 10 Mbps; 100 Mbps (Fast Ethernet)                                                                                                                                                                        |
| Network Management Card Description                         | Network management card included                                                                                                                                                                         |
| Communications Interface                                    | Contact closure; DB9 Serial; EPO (emergency power off); Pre-installed network card; Slot for SNMP/Web interface; USB                                                                                     |
| Emergency Power Off (EPO)/Remote On-Off (ROO)               | Yes                                                                                                                                                                                                      |
| <b>LINE / BATTERY TRANSFER</b>                              |                                                                                                                                                                                                          |
| Transfer Time                                               | 1-4ms for normal mode, >5ms for sensitive mode                                                                                                                                                           |
| Low Voltage Transfer to Battery Power (Setpoint)            | 160V (Normal Mode), 150V (Extended Mode)                                                                                                                                                                 |
| High Voltage Transfer to Battery Power (Setpoint)           | 294 (Normal/Extended Modes)                                                                                                                                                                              |
| <b>FEATURES &amp; SPECIFICATIONS</b>                        |                                                                                                                                                                                                          |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported                                                                                                                                                                           |
| High Availability UPS Features                              | Auto Probe Monitoring and Reboot (included); Automatic Voltage Regulation (AVR); Expandable battery backup; Hot swappable batteries; Remote management; Sine wave output; Surge/noise protection         |
| Green Energy-Saving Features                                | Greater than 95% efficiency - GREEN UPS; Individually controllable load banks                                                                                                                            |
| Grounding Details                                           | Rear panel grounding lug                                                                                                                                                                                 |
| <b>APPLICATIONS</b>                                         |                                                                                                                                                                                                          |
| UPS Applications                                            | Large Network; High-End Desktop/Small Network                                                                                                                                                            |
| <b>STANDARDS &amp; COMPLIANCE</b>                           |                                                                                                                                                                                                          |
| Product Certifications                                      | CAN/CSA C22.2; EN 62040-2; EN 62040-3; IEC 62040-2; UL 1778; cTUVus                                                                                                                                      |
| Product Compliance                                          | CE (Europe); ENERGY STAR Qualified; FCC Part 15 Class A (USA); RoHS; UKCA                                                                                                                                |
| <b>WARRANTY &amp; SUPPORT</b>                               |                                                                                                                                                                                                          |
| Product Warranty Period (Worldwide)                         | 2-year warranty, 3 year with registration. Note:&nbsp;<a class="insuranceLink" href="//tripplite.eaton.com/support/product-warranty-registration">Registration is required</a>&nbsp;for 3-year warranty. |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.